

## **Manufacturer of Unique High Quality Floors**

# **Tuscan**

### **Technical Specifications**

**Tuscan Series:** The Tuscan Series is designed to replicate that old world look of the way floors were made hundreds of years ago through the Tuscany regions of Italy. Everything about those old floors was done by hand. The multiple widths replicate the use of every piece of the tree cut to make each floor unique in its own way. The hand-scraping is done by craftsmen, with years of artisan experience, to give each board its own beautiful personality.

### PRODUCT INFORMATION

Construction: Engineered prefinished hardwood flooring with tongue and grooves

Species: Hickory / Walnut / Maple

Grade: Rustic (includes knots, splits, mineral streaks and filler)

Color Choice: Refer to Johnson's product sheet

Wear-Layer Thickness: Nominal 2.0 mm (Sliced cut) before hand-scraping

Overall Thickness: Nominal 9/16"

Core Material (Species)

Varies between Birch, Poplar and Eucalyptus

Width:

4 ½" (114.3 mm), 6" (152.4 mm), 7 ½" (190 mm)

Length: 11" to 71"

Style: Hand-scraped (except for Lucca, which is smooth finished, and the new colors:

Genoa, Catania, Arrezo and Prato where the surface has been wired-brushed).

Finish: Aluminum oxide particulates suspended in UV cured polyurethane

Luster: Semi-Gloss (except for the following colors which are matte level gloss of 5 ± 2

degrees: Genoa, Catania, Arrezo and Prato).

UV Sensitivity: Stains/Dyes can/will fade when exposed to UV light. Wood

(Depending on the species) can/will lighten and/or darken when

exposed to UV Light.

Color Tone/Variation: Moderate

**INSTALLATION:** Staple, Glue or Float (above, on, or below grade)

**Subfloor:** Refer to Guidelines

**PACKAGING** 

SQ/FT Per Carton: 41.5
Cartons Per Pallet: 30
Pounds Per Carton: 85

PERFORMANCE TEST METHOD RESULTS

Taber Abrasion: D4060 400 to 500 revolutions

Species Hardness Based on NWFA Janka: ASTM-D-143 Hickory (1820) American Walnut (1010)

Formaldehyde: CARB Phase 2 Compliant

#### WARRANTY

35-YEAR LIMITED STRUCTURAL AND FINISH WARRANTY (see warranty for further information).

WARNING: NOT TO BE INSTALLED NEAR OPEN FLAMES OR EXCESSIVE HEAT SOURCES, OR IN FULLY FUNCTIONAL BATH ROOMS, WHICH CONTAIN BATH TUBS AND/OR SHOWERS.